



Consolidated Edison Company of New York, Inc.

Electric Distribution Storm Hardening Initiatives



Paul V. Stergiou
Distribution Engineering
October 14th, 2015

Energy For New York City And Westchester

- 3.3 million electric customers
- Record System Load: 13,322 MW
- 36,000 miles of overhead transmission and distribution lines
- 94,000 miles of underground transmission and distribution lines
- 1.1 million gas customers
- 4,300 miles of gas mains
- 1,800 steam customers
- 105 miles of steam mains and lines
- 690 MW of regulated generation



Storm Preparations: Guided by Corporate Coastal Storm Plan

- Plan triggered Oct. 24 based on National Weather Service forecasts
- Reviewed:
 - 24/7 staffing plans
 - Equipment vulnerability
 - Inventories
 - Protection plans for equipment in flood zones
 - Need for outside assistance



Mutual Aid Base Camp at Rye Playland



Superstorm Sandy Details

- Storm Classification: Hurricane/ Extra-tropical
- Sustained winds of 64 mph at LaGuardia Airport with a peak gust of 90 mph on Staten Island
- NYC experienced approximately 30 hours of storm conditions
 - Storm tide recorded at the Battery – 14.06'
 - Largest Atlantic storm on record, spanning more than 1,000 miles
 - More than 8.5 million power outages across 21 states



Impact of Sandy


- 1.1 million customer outages
- Lost 4,000 MW of generation
- 60% of 345 kV feeders lost
- 5 transmission substations
 - 11 Manhattan networks
 - 3 Staten Island area stations
- 2 steam stations and 561 steam customers impacted
- 398 gas services interrupted



System Performance


Historical Storm Comparison

Electric Customers Interrupted



* includes outages caused by Nor'easter on Nov. 7, 2012

The East River: 14th Street and Avenue C




East River / E 13th Street Complex



Loss of Supply

East River Complex


Datum Diagram (Not to Scale)



Final Hardening Measures

2014 through 2016

- Distributed and elevation adjustable relay panels
- Elevate control house
- Elevate static terminal boxes
- Change controls to fiber optic
- Future design basis will accommodate new level for future projects




Storm Hardening UG Networks

Goals & Strategy

- Minimize preemptive feeder outages system wide
- Reduce damaged to equipment in the flood zone
- Reduce customer impact in flood zone networks
- Increase restoration speed for network shutdowns


Distribution Feeder Outages



Storm Hardening Initiatives

Underground Distribution

- Network Reconfiguration
- Utilize Latest Technology
- Harden Components
- Mitigate Impact
- Facilitate Restoration



New Sub-Networks

Underground Network Initiatives

High Tension Vaults - Isolation Switches

- Disconnects Customer Installation from Con Ed System
- Con Edison Feeder remains active
- Remote Control operation
- Quick Connect / Disconnect
- Faster Restoration Times



120V Network Protector Design Evolution

- Replaces & phases out ventilated cabinets



Ventilated End Mounted Cabinet




Submersible End Mounted Housing

Underground Network Initiatives

Overview


- Reconfiguration of Fulton and Bowling Green networks
- Installation of isolation switches for Brighton Beach network
- Installation of isolation switches for High Tension Vaults in 2013 FEMA 100 Year + 3 Feet Flood Zone
- Replacement of all non-submersible 120/208V equipment in Flood Zone
- Development of submersible 265/460V housing

System Overview



Benefits of New Partitioning System

- Minimize customer interruption
 - 1,789 Residential households
 - 441 Commercial
 - 46,745 Employees
- Faster Restoration
 - Substations remain online
 - Ability to restore individual circuits
- Transmission Planning Tool
- Year round benefit for feeder processing



Sandy's Impact:

Significant Damage to Overhead System

- 70 percent of customers served by overhead systems lost power
- Primary concern of safety
- Worked with city and municipalities to clear roads of trees and debris



Storm Recovery Pole & Transformer Usage			
	Poles	Transformers	Cable [miles]
Sandy Total CECONY	972	922	143.46
Irene Total CECONY	91	163	31.11


Improve Autoloop Reliability

- Additional supply feeders
- Divide large autoloops into smaller loops
- Upgrade wire and pole sizes to improve resiliency
- Use of more resilient aerial cable
- Sacrificial components to minimize damage

Overhead Distribution Initiatives

Auto Loop - Overview

- Extend new feeder
- Split Auto-loop into two loops
- New storm hardened cable



Storm Hardening Initiatives

Overhead Distribution

- Advanced Equipment
- Selective Undergrounding
- Reduce Segment Size
- Sacrificial Components



Spacer Cable

- Low profile design reduces risk of tree contact
- High strength messenger provides greater resilience against falling limbs
- Cable jacket reduces momentary outages from wind or incidental tree contact
- Compact configuration reduces tree trimming



Breakaway Connectors

- Service connection breaks away at pole when force exceeds 500lbs
- Service cable is disconnected and denergized
- Separate breakaway for each individual service
- Accommodates single, double or triple service configurations



Breakaway
Connection

Isolation Devices (Fused Bypass)



Selective Undergrounding

- Meeting with Municipalities to determine critical circuits to harden.




Harden Components: New Pole Designs



Enhanced Line Clearance Program

- Foundation program continued to ensure 10 X 10 X 15 Clearance every three years is achieved on High Voltage Feeders.
- Increased removal of damaged or unhealthy hazard trees near High Voltage feeders
- Obtain additional clearance on High Voltage Feeders that have higher outage rates and affect customers more frequently
- Obtain additional clearance on Feeders where we are performing significant Storm Hardening work







Consolidated Edison Company of New York, Inc.



Electric Distribution Storm Hardening Initiatives



Paul V. Stergiou
Distribution Engineering
October 14th, 2015